

DAFTAR PUSTAKA

- [1] Y. Zhu, H. Wu, and J. Zhang, "Regenerative Braking Control Strategy for Electric Vehicles Based on Optimization of Switched Reluctance Generator Drive System," *IEEE Access*, vol. 8, pp. 76671–76682, 2020, doi: 10.1109/ACCESS.2020.2990349.
- [2] M. Korkosz and A. Powrózek, "The influence of control parameters on energy efficiency of switched reluctance generator for vehicle applications," *E3S Web Conf.*, vol. 14, p. 01037, Mar. 2017, doi: 10.1051/e3sconf/20171401037.
- [3] Z. Zhang, R. Ma, L. Wang, and J. Zhang, "Novel PMSM Control for Anti-Lock Braking Considering Transmission Properties of the Electric Vehicle," *IEEE Trans. Veh. Technol.*, vol. 67, no. 11, pp. 10378–10386, Nov. 2018, doi: 10.1109/TVT.2018.2866828.
- [4] G. D. Wahyu and S. Riyadi, "PWM Control Strategy of Regenerative Braking to Maximize The Charging Current into The Battery in SRM Drive," in *2019 International Seminar on Application for Technology of Information and Communication (iSemantic)*, Sep. 2019, pp. 523–527, doi: 10.1109/ISEMANTIC.2019.8884342.
- [5] A. F. Dewi and S. Riyadi, "The Impact of SRM Rotor Speed on Regenerative Braking to Optimize the Performance," *CENCON 2019 - 2019 IEEE Conf. Energy Convers.*, vol. 2019-Janua, no. 1, pp. 104–109, 2019, doi: 10.1109/CENCON47160.2019.8974687.
- [6] P. C. Buck, B. Fahimi, and P. T. Balsara, "A Phase Current Peak Prediction

Technique to Increase the Output Power of Switched Reluctance Generators for Wind Turbines,” in *2019 IEEE Energy Conversion Congress and Exposition (ECCE)*, Sep. 2019, pp. 5244–5250, doi: 10.1109/ECCE.2019.8912691.

- [7] A. R. Haryawan, “Energy Efficient C-Dump Converter with Inductor for Switched Reluctance Motor,” *2018 IEEE 16th Student Conf. Res. Dev. SCOReD 2018*, no. 1, pp. 2–6, 2019, doi: 10.1109/SCORED.2018.8710794.
- [8] M. Ma, Z. Chang, Y. Hu, F. Li, C. Gan, and W. Cao, “An Integrated Switched Reluctance Motor Drive Topology with Voltage-Boosting and On-Board Charging Capabilities for Plug-In Hybrid Electric Vehicles (PHEVs),” *IEEE Access*, vol. 6, pp. 1550–1559, 2017, doi: 10.1109/ACCESS.2017.2779460.
- [9] D. Scharfenstein, B. Burkhart, and R. W. De Doncker, “Influence of an FPGA-based switching angle dithering on acoustics in single-pulse controlled switched reluctance machines,” in *2015 IEEE 11th International Conference on Power Electronics and Drive Systems*, Jun. 2015, vol. 2015-Augus, no. June, pp. 754–761, doi: 10.1109/PEDS.2015.7203471.
- [10] V. Wijaya and S. Riyadi, “Implementation of Input Capture Method on Switched Reluctance Motor to Obtain Precise Commutation Signals,” *CENCON 2019 - 2019 IEEE Conf. Energy Convers.*, vol. 2019-Janua, pp. 110–114, 2019, doi: 10.1109/CENCON47160.2019.8974776.
- [11] M. Nur Saiful Hakim and S. Riyadi, “The use of input capture method to

- increase torque on switched reluctance motor,” *J. Phys. Conf. Ser.*, vol. 1444, no. 1, 2020, doi: 10.1088/1742-6596/1444/1/012014.
- [12] G. Ji and K. Ohyama, “Simulation of Wind Power Generation System Using Switched Reluctance Generator and Capacitor-less AC-AC converter,” in *2018 International Power Electronics Conference (IPEC-Niigata 2018 -ECCE Asia)*, May 2018, pp. 2921–2926, doi: 10.23919/IPEC.2018.8507528.
- [13] L. Ling, L. Dong, and X. Liao, “Comparison of two control methods of switched reluctance generator,” in *2017 12th IEEE Conference on Industrial Electronics and Applications (ICIEA)*, Jun. 2017, vol. 2018-Febru, no. 4, pp. 792–796, doi: 10.1109/ICIEA.2017.8282947.
- [14] S. Riyadi, “Analysis of C-Dump Converter for SRM Drives,” in *2018 International Conference on Electrical Engineering and Informatics (ICELTICS)(44501)*, Sep. 2018, no. c, pp. 179–184, doi: 10.1109/ICELTICS.2018.8548791.