

DAFTAR PUSTAKA

- [1] D. A. Torrey, “Switched reluctance generators and their control,” *IEEE Trans. Ind. Electron.*, vol. 49, no. 1, pp. 3–14, 2002, doi: 10.1109/41.982243.
- [2] P. Kerdtuad and S. Kittiratsatcha, “Study of maximum power conversion of a switched-reluctance generator,” *ECTI-CON 2011 - 8th Electr. Eng. Electron. Comput. Telecommun. Inf. Technol. Assoc. Thail. - Conf. 2011*, no. 1, pp. 633–636, 2011, doi: 10.1109/ECTICON.2011.5947919.
- [3] S. Sartori, M. Basu, M. Farrell, and A. Tortella, “Simulation and analysis of switched reluctance generator for renewable energy applications,” *Proc. - 2016 51st Int. Univ. Power Eng. Conf. UPEC 2016*, vol. 2017–Janua, pp. 1–6, 2016, doi: 10.1109/UPEC.2016.8114081.
- [4] G. D. Wahyu and S. Riyadi, “PWM Control Strategy of Regenerative Braking to Maximize the Charging Current into the Battery in SRM Drive,” *Proc. - 2019 Int. Semin. Appl. Technol. Inf. Commun. Ind. 4.0 Retrospect. Prospect. Challenges, iSemantic 2019*, pp. 523–527, 2019, doi: 10.1109/ISEMANTIC.2019.8884342.
- [5] V. Wijaya and S. Riyadi, “Implementation of Input Capture Method on Switched Reluctance Motor to Obtain Precise Commutation Signals,” *CENCON 2019 - 2019 IEEE Conf. Energy Convers.*, vol. 2019–Janua, pp. 110–114, 2019, doi: 10.1109/CENCON47160.2019.8974776.
- [6] S. Mapa, R. Maheswari, and G. Bhuvaneswari, “Maximum Power Point Tracking Using a Novel Current Control Strategy in an SRG Based Variable Speed Wind Energy Conversion System,” *India Int. Conf. Power Electron.*

- IICPE*, vol. 2018–Decem, pp. 1–5, 2018, doi: 10.1109/IICPE.2018.8709471.
- [7] M. Korkosz and A. Powrózek, “The influence of control parameters on energy efficiency of switched reluctance generator for vehicle applications,” *E3S Web Conf.*, vol. 14, 2017, doi: 10.1051/e3sconf/20171401037.
- [8] M. Nur Saiful Hakim and S. Riyadi, “The use of input capture method to increase torque on switched reluctance motor,” *J. Phys. Conf. Ser.*, vol. 1444, no. 1, 2020, doi: 10.1088/1742-6596/1444/1/012014.
- [9] S. S. Ahmad and G. Narayanan, “Modeling of Single-Pulse Operated Switched Reluctance Generator and Its Verification,” *IEEE Trans. Ind. Appl.*, vol. 56, no. 5, pp. 4966–4976, 2020, doi: 10.1109/TIA.2020.3005586.
- [10] A. F. Dewi and S. Riyadi, “The Impact of SRM Rotor Speed on Regenerative Braking to Optimize the Performance,” *CENCON 2019 - 2019 IEEE Conf. Energy Convers.*, vol. 2019–Janua, no. 1, pp. 104–109, 2019, doi: 10.1109/CENCON47160.2019.8974687.
- [11] L. J. Lemes, V. Regis Bernardeli, L. C. Gomes, D. Alves De Andrade, G. P. Viajante, and M. Antonio Arantes De Freitas, “Dynamic Analysis of Self-excited SRG Operating in Open Loop,” *2019 IEEE 15th Brazilian Power Electron. Conf. 5th IEEE South. Power Electron. Conf. COBEP/SPEC 2019*, 2019, doi: 10.1109/COBEP/SPEC44138.2019.9065484.
- [12] V. Nasirian, S. Kaboli, and A. Davoudi, “Output power maximization and optimal symmetric freewheeling excitation for switched reluctance generators,” *IEEE Trans. Ind. Appl.*, vol. 49, no. 3, pp. 1031–1042, 2013, doi: 10.1109/TIA.2013.2253438.

- [13] P. C. Buck, B. Fahimi, and P. T. Balsara, “A Phase Current Peak Prediction Technique to Increase the Output Power of Switched Reluctance Generators for Wind Turbines,” *2019 IEEE Energy Convers. Congr. Expo. ECCE 2019*, pp. 5244–5250, 2019, doi: 10.1109/ECCE.2019.8912691.
- [14] S. Dong *et al.*, “Threshold voltage improvement scheme for high-voltage IGBT,” *2019 IEEE 3rd Int. Conf. Electron. Inf. Technol. Comput. Eng. EITCE 2019*, pp. 390–393, 2019, doi: 10.1109/EITCE47263.2019.9094813.
- [15] S. Boksuwan and T. Benjanarasuth, “Code generation of fractional filters for dsPIC microcontrollers,” *IEEE Reg. 10 Annu. Int. Conf. Proceedings/TENCON*, pp. 1275–1279, 2011, doi: 10.1109/TENCON.2011.6129012.

