

## DAFTAR PUSTAKA

- [1] H. C. Wu, M. Y. Wen, and C. C. Wong, "Speed control of BLDC motors using hall effect sensors based on DSP," *2016 IEEE Int. Conf. Syst. Sci. Eng. ICSSE 2016*, 2016.
- [2] H. Aulia Rahman and S. Riyadi, "Pengaruh Duty Cycle Terhadap Perpindahan Energi Pada Motor Bldc (Brushless Direct Current) Saat Pengereman Regeneratif Berbasis Dspic30F4012," pp. 247–254, 2019.
- [3] A. Mohammad and M. Z. R. Khan, "BLDC motor controller for Regenerative Braking," *2nd Int. Conf. Electr. Eng. Inf. Commun. Technol. iCEEICT 2015*, no. May, pp. 21–23, 2015.
- [4] I. W. A. Nugroho and S. Riyadi, "Regenerative Braking with Duty Cycle Settings for Brushless DC Motor," *Proc. Int. Conf. Electr. Eng. Informatics*, vol. 2019-July, no. July, pp. 336–341, 2019.
- [5] F. T. Industri, "Desain Dan Implementasi Interleaved Boost," 2014.
- [6] N. Boujelben, F. Masmoudi, M. Djemel, and N. Derbel, "Modeling and comparison of boost converter with cascaded boost converters," *Green Energy Technol.*, pp. 85–103, 2019.
- [7] M. A. Mazta, A. S. Samosir, and A. Haris, "Rancang Bangun Interleaved Boost Converter Berbasis Arduino," *J. Rekayasa dan Teknol. Elektro*, vol. 10, no. 1, pp. 22–29, 2016.
- [8] H. Matalata and L. W. Johar, "ANALISA BUCK CONVERTER DAN BOOST CONVERTER PADA PERUBAHAN DUTY CYCLE PWM

DENGAN MEMBANDINGKAN FREKUENSI PWM 1,7 Khz DAN 3,3 Khz,” *J. Ilm. Univ. Batanghari Jambi*, vol. 18, no. 1, p. 42, 2018.

- [9] A. Fathah, “Design of a Boost Converter,” *Fathah, A. (2013). Des. a Boost Convert. 2. Retrieved from <http://ethesis.nitrkl.ac.in/4811/1/109EE0612.pdf>*, p. 2, 2013.
- [10] D. Harselina, “Rancang Bangun Boost Converter,” pp. 11–17, 2019.
- [11] N. Boujelben, F. Masmoudi, M. Djemel, and N. Derbel, “Design and comparison of quadratic boost and double cascade boost converters with boost converter,” *2017 14th Int. Multi-Conference Syst. Signals Devices, SSD 2017*, vol. 2017-Janua, pp. 245–252, 2017.
- [12] G. Narayanan, “Computationally efficient models for simulation of non-ideal DC – DC Computationally efficient models for simulation of non-ideal DC – DC converters operating in continuous,” no. July, 2017.
- [13] A. P. Electronics, “Section 3 : Effect of Non-Ideal Switches And Components On DC-DC Converters,” vol. 1, pp. 1–34.
- [14] M. Lotfi Nejad, B. Poorali, E. Adib, and A. A. M. Birjandi, “New cascade boost converter with reduced losses,” *IET Power Electron.*, vol. 9, no. 6, pp. 1213–1219, 2016.
- [15] F. L. Tofoli, D. de C. Pereira, W. J. de Paula, and D. de S. Oliveira Júnior, “Survey on non-isolated high-voltage step-up dc-dc topologies based on the boost converter,” *IET Power Electron.*, vol. 8, no. 10, pp. 2044–2057, 2015.
- [16] M. Z. Malik, A. Ali, and D. Kumar, “A Two Cascaded Boost Converter with High Voltage Gain Module,” *Int. J. Comput. Electr. Eng.*, vol. 9, no.

- 2, pp. 476–483, 2017.
- [17] S. Riyadi, *Konverter Statis : Chopper dan PWM Rectifier serta Aplikasinya*. 2018.
- [18] T. H. Li, J. Wang, and H. S. H. Chung, “Effect of parasitic elements in a power converter on the switching performance of a MOSFET-snubber-diode configuration,” *Conf. Proc. - IEEE Appl. Power Electron. Conf. Expo. - APEC*, pp. 364–371, 2011.
- [19] J. Jovalusky, “New low reverse recovery charge (QRR) high-voltage silicon diodes provide higher efficiency than presently available ultrafast rectifiers,” *Conf. Proc. - IEEE Appl. Power Electron. Conf. Expo. - APEC*, pp. 918–923, 2008.
- [20] A. Kumar and R. K. Singh, “Power loss calculation of diode assisted cascaded Quasi-Z-source converter with CCM and DCM operation,” *2016 IEEE 6th Int. Conf. Power Syst. ICPS 2016*, 2016.
- [21] Z. Istataqomawan, D. Darjat, and A. Warsito, “Catu Daya Tegangan DC Variabel dengan Dua Tahap Regulasi ( Switching dan Linier ),” pp. 1–8, 2019.
- [22] R. S. Putra, N. Hariyanto, and S. Saodah, “Perancangan Dan Realisasi Converter Satu Fasa untuk Baterai Menjalankan Motor AC 1 Fasa 125 Watt,” *Reka Elektron.*, vol. 4, no. 1, pp. 1–15, 2016.