

## DAFTAR PUSTAKA

- [1] A. A. Memon, U. Yasir, and M. A. Uquali, "Calculation of converter losses for switched reluctance motor," *2017 20th Int. Conf. Electr. Mach. Syst. ICEMS 2017*, no. c, 2017, doi: 10.1109/ICEMS.2017.8056533.
- [2] A. Shehada, S. Member, and R. Krishnan, "Low-Cost Single-Switch Variable-Speed Switched Reluctance Motor Drive," doi: 10.1109/IEMDC.2015.7409180.
- [3] J. Cai, L. Lu, Z. Liu, H. Jia, X. Zhao, and F. Xu, "An inductive position sensor with switched reluctance motor structure," *2017 20th Int. Conf. Electr. Mach. Syst. ICEMS 2017*, pp. 12–15, 2017, doi: 10.1109/ICEMS.2017.8056495.
- [4] L. E, B. R, P. F, T. H.A., and W. S, "Multiphase induction motor drives-a technology status review," *IET Electr. Power Appl.*, vol. 1, no. 5, pp. 643–656, 2007, doi: 10.1049/iet-epa.
- [5] Y. Saleem and T. Izhar, "Control of torque in switched reluctance motor," *2nd Int. Conf. Electr. Eng. ICEE*, no. March, pp. 8–11, 2008, doi: 10.1109/ICEE.2008.4553904.
- [6] S. Riyadi, *Konverter Statis untuk Penggerak Motor Switched Reluctance*. 2019.
- [7] S. Riyadi, "Control strategy for switched reluctance motor with rotary encoder based rotor position detection," *Adv. Electr. Electron. Eng.*, vol. 16, no. 3, pp. 261–270, 2018, doi: 10.15598/aeec.v16i3.2545.
- [8] S. Riyadi, "A simple method to control the excitation angle for switched

- reluctance motor,” *Indones. J. Electr. Eng. Informatics*, vol. 9, no. 2, pp. 384–393, 2021, doi: 10.52549/ijeei.v9i2.2814.
- [9] Y. Nakazawa, K. Ohyama, H. Fujii, H. Uehara, and Y. Hyakutake, “Improvement of efficiency of switched reluctance motor by single pulse control based on linear torque equation,” *2013 15th Eur. Conf. Power Electron. Appl. EPE 2013*, 2013, doi: 10.1109/EPE.2013.6634418.
- [10] I. Marouf, M. M. Asad, A. Bakhuraibah, and Q. A. Al-haija, “Adders Using Altera Cyclone IV FPGA Kit,” pp. 8–11, 2017, doi: 10.1109/ICECTA.2017.8252011.
- [11] Q. A. Al-Haija, M. Al-Ja’Fari, and M. Smadi, “A comparative study up to 1024 bit Euclid’s GCD algorithm FPGA implementation and synthesizing,” *Int. Conf. Electron. Devices, Syst. Appl.*, 2017, doi: 10.1109/ICEDSA.2016.7818535.
- [12] S. C. Huerta, A. de Castro, O. García, and J. A. Cobos, “FPGA-based digital pulsewidth modulator with time resolution under 2 ns,” *IEEE Trans. Power Electron.*, vol. 23, no. 6, pp. 3135–3141, 2008, doi: 10.1109/TPEL.2008.2005370.
- [13] V. Wijaya and S. Riyadi, “Implementation of Input Capture Method on Switched Reluctance Motor to Obtain Precise Commutation Signals,” *CENCON 2019 - 2019 IEEE Conf. Energy Convers.*, vol. 2019-Janua, pp. 110–114, 2019, doi: 10.1109/CENCON47160.2019.8974776.
- [14] L. Zhang and C. Liu, “A Sensorless Techniques for Switched Reluctance Motor Considering Mutual Inductances,” *Proc. 2020 IEEE 5th Inf. Technol.*

*Mechatronics Eng. Conf. ITOEC 2020*, no. Itoec, pp. 1425–1428, 2020, doi: 10.1109/ITOEC49072.2020.9141636.

- [15] E. Ofori, T. Husain, Y. Sozer, and I. Husain, “A Pulse-Injection-Based Sensorless Position Estimation Method for a Switched Reluctance Machine Over a Wide Speed Range,” *IEEE Trans. Ind. Appl.*, vol. 51, no. 5, pp. 3867–3876, 2015, doi: 10.1109/TIA.2015.2420618.
- [16] A. D. Wardani, S. Riyadi, L. H. Pratomo, and F. B. Setiawan, “Peningkatan Efisiensi Kinerja Switched Reluctance Motor dengan Metode Pergeseran Sudut Fasa,” vol. 42, no. 3, pp. 253–259, 2021, doi: 10.14710/teknik.v42i3.
- [17] T. Wasita Febriandi and S. Riyadi, “Pengaturan Kecepatan Motor Switched Reluctance Dengan Konverter Asymmetric Pada Mode Magnetizing Dan Demagnetizing,” pp. 269–276, 2019, doi: 10.5614/sniko.2018.32.