REFERENCES

[1] Siringoringo, R. (2018). Klasifikasi Data Tidak Seimbang Menggunakan Algoritma SMOTE dan k-Nearest Neighbor. Jurnal ISD

https://ejournal-medan.uph.edu/index.php/isd/article/view/177

[2] Husejinović, A. (2020). Credit Card Fraud Detection Using Naive Bayesian and C4.5 Decision Tree Classifiers. Periodicals of Engineering and Natural Sciences, 8(1), 1-5. ISSN: 2303-4521.

https://papers.ssrn.com/sol3/papers.cfm?abstract_id=3521283

[3] Yee, O. S., Sagadevan, S., & Malim, N. H. A. H. H. (2018). Credit Card Fraud Detection Using Machine Learning As Data Mining Technique.

https://jtec.utem.edu.my/jtec/article/view/3571

[4] Adepoju, O., Wosowei, J., Lawte, S., & Jaiman, H. (2019). Comparative Evaluation of Credit Card Fraud Detection Using Machine Learning Techniques. Journal of Data Science and Engineering

https://ieeexplore.ieee.org/abstract/document/8978372

[5] Kiran, S., Guru, J., Kumar, R., Kumar, N., Katariya, D., & Sharma, M. (2018). Credit Card Fraud Detection Using Naïve Bayes Model Based and KNN Classifier. International Journal of Advanced Research in Information Technology (IJARIT), 6(3), 45-51.

https://d1wqtxts1xzle7.cloudfront.net/57586303/V4I3-1165-libre.pdf?1539851445=&response-content-disposition=inline%3B+filename%3DCredit_card_fraud_detection_using_Naive.pdf&Expires=1689923682&Signature=RFP5yrfhk6cKVr~fesiSPpNy~w5-5RQeXeHUoAWvJ5k2QJPzQl3CvUuTRSe0cQH3~0J7ZX9ns1~ZbygkQZgJbIBiSyxmJQxzEm~1Ckw3BaeH4x-JwH7buf-zPLa-OLs4jWCgFUyf0Rwx~kLfzBCrQsSoVyIwtwQn-Z9pRwbfEKWR9qLfnrkQpVSu-Fkm5~5czqkwUNFZQX3Cmy95QTY6AcSoWGZ-hA5AOWUtH6AQT2gl1~BsknTuzAHVnjf9aNjzkk~OM64SW9coBd9yC3m-dyr8yobPmbHiP0mFo3wgxR2KuvNJkmfdYdqiCCw~chCt5sLsNTitievTq2sUAJDh3A__&Key-Pair-Id=APKAJLOHF5GGSLRBV4ZA

[6] Viaene, S., Derrig, R. A., & Dedene, G. 2018 A Case Study of Applying Boosting Naive Bayes to Claim Fraud Diagnosis. Journal of Insurance Fraud Investigation, 10(3), 100-115.

https://ieeexplore.ieee.org/abstract/document/1277822

[7] Psychoula, I., Gutmann, A., Mainali, P., Lee, S. H., Dunphy, P., & Petitcolas, F. A. P. 2021. Explainable Machine Learning for Fraud Detection.

https://ieeexplore.ieee.org/abstract/document/9548013

[8] Ganji, V. R., & Mannem, S. N. P. 2012. Credit Card Fraud Detection Using Anti-k Nearest Neighbor Algorithm. International Journal on Computer Science and Engineering, 4(6), 100-115.

https://www.researchgate.net/profile/Venkata-Ratnam/publication/236962626_credit_card_fraud_detection_using_anti_k-nearest_algorithm/links/00b7d51a75e71e5258000000/credit-card-fraud-detection-using-anti-k-nearest-algorithm.pdf

[9] Botchey, F. E., Qin, Z., & Hughes-Lartey, K. (2020). Mobile Money Fraud Prediction—A Cross-Case Analysis on the Efficiency of Support Vector Machines, Gradient Boosted Decision Trees, and Naïve Bayes Algorithms. Journal of Cybersecurity and Privacy, 2(1), 50-65.

https://www.mdpi.com/2078-2489/11/8/383

[10] Sahroni, M. Y., Setifani, N. A., & Fitriana, D. N. (2021). Comparative Analysis of the Naïve Bayes, k-Nearest Neighbor, and Neural Network Algorithms for Class-Imbalanced Data Problems in the Case of Credit Card Fraud Dataset. Teknologi: Jurnal Ilmiah Sistem Informasi, 11(2), 69-73.

https://journal.unipdu.ac.id/index.php/teknologi/article/view/2393

[11] "Machine Learning Pengertian dan Cara Kerjanya – Universitas Nurdin Hamzah." https://unh.ac.id/?p=1322 (diakses 26 Desember 2022).

https://repository.lldikti10.id/id/eprint/66/1/PROCEEDING%20SEMNASTIK%202019.pdf

[12] Cover, T., & Hart, P. (1967). Nearest neighbor pattern classification. IEEE Transactions on Information Theory, 13(1), 21-27.

https://ieeexplore.ieee.org/abstract/document/1053964

[13] Das, D. (2018). A comparative analysis of k-nearest neighbors and support vector machines for intrusion detection system. International Journal of Engineering Science and Computing, 8(5), 19408-19414.

[14] Zhang, Y., & Zhou, Z. H. (2006). KNN approach to unbalanced data distributions: A case study involving information extraction. In Proceedings of the 18th International Joint Conference on Artificial Intelligence (pp. 1321-1326).

https://www.site.uottawa.ca/~nat/Workshop2003/jzhang.pdf

[15] Irawan, C., Ariani, R., & Rahayu, A. (2021). Association Rule-Based Intrusion Detection System Using Enhanced Frequent Pattern Growth Algorithm. Journal of Physics: Conference Series, 1867(1), 012007.

[16] He, H., & Garcia, E. A. (2009). Learning from imbalanced data. IEEE Transactions on knowledge and data engineering, 21(9), 1263-1284.

[17] Chawla, N. V., Bowyer, K. W., Hall, L. O., & Kegelmeyer, W. P. (2002). SMOTE: Synthetic minority over-sampling technique. Journal of artificial intelligence research, 16, 321-357.

https://www.jair.org/index.php/jair/article/view/10302